


Karakteristikler



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- inko kaplama elik levhadan yap?lm?? kendini ta??yan kasa yap?s?, standart olarak yap?sall epoksi-polyester RAL9016 beyaz boyayla cilalan?r.Paslanmaz elik veya di?er renkler iste?e tabiidir.
- A??r? bak?m gerektirmeyen b?y?k fasetli hava giri?i ?zgaras?.
- Anodize edilmi? al?üminyum priz pervaneleri, kanat ?eklinde, iki tarafta da 0'dan 15°e kadar ayarlanabilir.
- D?ü?k ses seviyeli ve d??tan rotor motorlar?yla hareket eden ift giri?li santrüf? motorlar?. 5-h?z seviyeli.EC modelleri d?ü?k t?ketimli verimli fanlar ierir.
- "A" tipi ?s?tmas?z, sadece hava ile.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Ki?iselle?tirme

50Hz

Model	Is?nmam??	
	(m ³ /h)	(m)
TWIN KECG 3000 A	9,8-13,8	
TWIN KM 1500 A	9,8-13,1	
TWIN KM 2000 A	9,8-13,1	
TWIN KM 2500 A	9,8-13,1	
TWIN KM 3000 A	9,8-13,1	
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	
TWIN KG 1500 A	9,8-13,1	
TWIN KG 2000 A	9,8-13,1	
TWIN KG 2500 A	9,8-13,1	
TWIN KG 3000 A	9,8-13,1	
TWIN KECG 1500 A	9,8-13,8	
TWIN KECG 2000 A	9,8-13,8	
TWIN KECG 2500 A	9,8-13,8	

60Hz

Is?nmam??

Model	(m ³ /h)	(m)
TWIN KECM 1500 A	9,8-13,8	
TWIN KECM 2000 A	9,8-13,8	
TWIN KECM 2500 A	9,8-13,8	
TWIN KECM 3000 A	9,8-13,8	

Boyutlar

