



Karakteristikler

Dü?ük basınçlı GIRINTİLİ ARIS hava perdesi

- Çinko kaplama çelik levhadan yap?lm?? kendini ta??yan kasa yap?s?, asma tavana monte edilmek için haz?r.
- It has both internal and external fixings. Electrical and electronic connections inside.
- Tek bir çerçeve rengi RAL9016 ile kaplanm??, alüminyum profilleri ve üfleme ba?l???yla yap?lm?? hava giri?i ?zgaras?(bak?m gerektirmez).Di?er renkler iste?e tabiidir.
- Anodize edilmi? alüminyum priz pervaneleri, kanat ?eklinde.
- 2-h?zl? d??tan rotor motoru taraf?ndan hareket ettirilen dü?ük sesli bükümlü çapraz ak?m fanlar?.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. "E" tipi elektrik korumal? elementler, birle?ik ayarl? üç evre."A" tipi ?s?tmas?z, sadece hava ile.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Ki?iselle?tirme

50Hz

Is?nmam??			
Model	(m ³ /h)		(m)
RA 1000 A	2,5-3,5		
RA 1500 A	2,5-3,5		
RA 2000 A	2,5-3,5		

Elektrikli Is?tma			
Model	(m ³ /h)	(kW)	(m)
RA 1000 E	2,5-3,5		
RA 1500 E	2,5-3,5		
RA 2000 E	2,5-3,5		

Su Is?tma			
Model	(m ³ /h)	(kW)	(m)
RA 1000 P86	2,5-3,5		
RA 1500 P86	2,5-3,5		
RA 2000 P86	2,5-3,5		
RA 1000 P64	2,5-3,5		
RA 1500 P64	2,5-3,5		
RA 2000 P64	2,5-3,5		

60Hz



Is?nmam??		
Model	(m³/h)	(m)
RA 1000 A 60Hz	2,5-3,5	
RA 1500 A 60Hz	2,5-3,5	
RA 2000 A 60Hz	2,5-3,5	

Boyutlar

Dü?ük bas?nç? GIRINTILI ARIS hava perdesi - Boyutlar